

MINI OTDR 26/24



INSTRUMENT CHARACTERISTICS

- 1、 NINE-IN-ONE FUNCTION
- 2、 THE 4.3-INCH FULL-VIEW CAPACITIVE TOUCH SCREEN SUPPORTS MULTI-TOUCH
- 3、 COVER PLATE TYPE TEMPERED GLASS PANEL, DON'T WORRY ABOUT SCREEN SCRATCH
- 4、 SUPPORT HORIZONTAL VERSION, VERTICAL VERSION, PERFECT FUSION OF THE TWO HABITS OF USER OPERATIONS
- 5、 SUPPORT CHARGING TREASURE CHARGING, DO NOT WORRY ABOUT THE BATTERY IS NOT ENOUGH
- 6、 IN LINE WITH THE INTERNATIONAL STANDARDS OF TEST DATA WITH PERFECT SIMULATION SOFTWARE, SO THAT YOUR REPORT MORE SIMPLE
- 7、 SINK TYPE LIGHT PORT DESIGN, SO THAT THE INSTRUMENT LIGHT PORT TO GET BETTER PROTECTION
- 8、 SUPPORT U DISK, SD CARD AND MICRO USB EXPORT DATA PROTECTION
- 9、 ANY INTERFACE SUPPORTS SCREEN CAPTURE

PHYSICAL INDICATORS

- 1、 4.3-INCH CAPACITIVE TOUCH SCREEN WITH FULL VIEWING , TFT 800X480 RESOLUTION
- 2、 LITHIUM BATTERY: 5200MAH/ 3.7V, STANDBY TIME > FOR 10 HOURS
- 3、 SIZE: 175X105X45MM, WEIGHT: 560G (INCLUDING BATTERY)
- 4、 WORKING TEMPERATURE: -10~+55°C, STORAGE TEMPERATURE: -20~+80°C

MINI OTDR 26/24



SPECIFICATION

SPECIFICATIONS MODEL	T-OT560-A26D
Wavelength	1310/1550
Dynamic	26/24 dB
Fiber type	G.652D
Event dead zone	1.5m
Attenuation zone	7 m
Measuring range	100m、 500m、 2km、 5km、 10km、 20km、 40km、 80km/90km
Sampling resolution	20cm~8m
The sampling point	Maximum sampling points : 20000
Linearity	≤0.05dB/dB
Loss threshold	0.01dB
Loss resolution	0.001dB
Refractive index	1 .0000~2 .0000
Range resolution	0.01m
Range accuracy	±(0.5m+Range×3×10-5+Sampling resolution) (Excluding refractive index error)
Reflection accuracy	±3d B
File format	Standard sor file format
Safety level	Class 3B
Temperature	Working temperature : -10°C~+55°C ; Storage temperature : -20°C~+80°C
Humidity	≤95% (No condensation)

MINI OTDR 26/24



SPECIFICATION

OPM		LS (Only single mode)		Other	
Wavelength	850/ 1300/ 1310/ 1490/ 1550/ 1625/ 1650nm	Wavelength	OTDR wavelength	VFL	≥10mW
Range	A:-70~+10dBm B:-50~+26dBm	Laser type	FP - LD	RJ45	Line sequence / line finding
Frequency	270Hz/330Hz/ 1kHz/2kHz	Power	-5dB m±2dB (Adjust)	Battery	5200mAh/3 .7V
Uncertainty	±5%	Uncertainty	±5%	Adapter	USB(Type C)
Connector	Universal:FC/SC /ST	Connector	FC/SC/ST	Memory	Inside≥1000, External:SD

PICTURE

