

# CAJAS DE EMPALME DE 48 / 96F



## SPECIFICATION

Fiber Optic Splice Closure can be used in manhole, in handhole, aerial-hanger, wall-mounting, be directly buried and pedestal.



## DIMENSION

Height:53cm,

Base diameter:16cm

closet ring dia. :21cm

4 small holes +1 oval hole

The diameter of the small holes is 2.0cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.

Max. Fiber Capacity: 24×6=144 fibers

IP degree: IP 68

Working temperature: 40 degree ~ 110 degree

warranty: 25 years

Materials: closure body: PP splice tray: ABS

## CONTENT OF FIBER OPTIC SPLICE CLOSURE

- 1.Outer fixing part
- 2.Clamp
- 3.Dome
- 4.Base
- 5.Splice tray
- 6.Tray lid
- 7.Shield continuity wires

- 8.Valve
- 9.Shield continuity connector
- 10.Sealing ring
- 11.Inner fixing part
- 12.Strength member
- 13.Support ring on the base
- 14.Velcro strip with one X flake

# CAJAS DE EMPALME DE 48 / 96F



## OVAL OUTLET CABLE SEAL KIT

- 1.Heat shrinkable sleeve
- 2.Aluminum cable protection tapes
- 3.Abrasive strip
- 4.Branch off clip



## CABLE SEAL KIT

- 1.Aluminum cable protection tape
- 2.Heat shrinkable sleeve
- 3.Abrasive strip

## OTHER ACCESSORIES

- 1.Desiccant
- 2.Shield continuity wires
- 3.Connector
- 4.Smouvs (splicing protection tubing)
- 5.transparent tubes Tie wraps

