

CONECTORES PREMIUM SC APC /UPC



RELEVANT SOLUTIONS

- Easy operating, The connector can be directly used in ONU, also with fasten strength more than 5 kg, it is widely used in FTTH project of network revolution. It also reduce the use of sockets and adapters, save cost of project.
- With 86 standard socket and adapter, the connector makes connection between drop cable and patch cord. The 86 standard socket provides complete protection with its unique design.
- Applicable to connection with field mountable indoor cable, pigtail, patch cord and transformation of terminal box, distribution frame, ODF and patch cord.

DESCRIPTION



1. Screw boot clamping.
2. Transparent side Cover, visible for Inspection.
3. Specific coating stripper/cutting guideway.
4. Suitable for narrow installation space.
5. Applicable to bow-type drop cable and 2.0/3.0 indoor cable.

Item	Parameter
Cable Scope	3.0 x 2.0 mm Bow-type Drop Cable 2.0/3.0 indoor cable
Fiber Diameter	125μm (652 & 657)
Coating Diameter	250μm
Mode	SM
Operation Time	about 15s(exclude fiber presetting)
Insertion Loss	≤ 0.3dB (310nm & 1550nm)
Return Loss	≤ -50dB for UPC, ≤ -55dB for APC
Success Rate	>98%
Reusable Times	>10 times